



## CONTEXT OF THE CUSTOMER'S CHALLENGE

**Place:** Turkey

**Application:** Quarrying and Mining /Drilling machine

**Usage conditions:** harsh environment with water infiltration, contamination and abrasive particles

**Customer requirements:** limit regular failures and increase the bearing life time

**Product in use:** 6208 with seals

## NTN'S RECOMMENDATION

Due to highly abrasive conditions:

- Negative impact on lubrication has been detected
- Following expertise, recommendation to reinforce the sealing properties of the bearing
- Test of NTN's **6208LLUCM/5K**, fitted on 3 machines
- Special design of the seal and the inner ring groove for high performance sealing



## RESULTS

- ▶ **Service life is at least increased by a factor of 3** compared to the sealed solution previously mounted.

	Number of maintenance periods (per year)	Total maintenance + gear cost (per year)
Previous solution	9	15 120 €
<b>NTN Ball Bearing with LLU</b>	<b>3</b>	<b>5 040 €</b>



**NTN LLU SEAL: FOR OPTIMAL AND LASTING PROTECTION!**



Polluted to heavily polluted environment



Excellent water and particle resistance



Maximum lubrication retention

**ANNUALIZED COST SAVINGS**

**10 080 €**

Reduced maintenance intervals  
Less spare part usage

This document is the exclusive property of NTN-SNR ROULEMENTS. Any total or partial reproduction hereof without the prior consent of NTN-SNR ROULEMENTS is strictly prohibited. Legal action may be brought against anyone breaching the terms of this paragraph. NTN-SNR ROULEMENTS shall not be held liable for any errors or omissions that may have crept into this document despite the care taken in drafting it. Due to our policy of continuous research and development, we reserve the right to make changes without notice to all or part of the products and specifications mentioned in this document. © NTN-SNR ROULEMENTS, international copyright 2022.